

What is claimed is:

Sub  
B7

1. An optical printing head of a side-printing device for printing data of a photosensitive material as a latent image on a side margin of said photosensitive material while said photosensitive material is being conveyed in a direction, said optical printing head comprising:

a plurality of light emitting elements mounted on a substrate and arranged along a perpendicular direction to the conveying direction of said photosensitive material;

a partitioning device mounted on said substrate, for partitioning said light emitting elements from each other, to prevent interference between rays from adjacent ones of said light emitting elements;

a diffusion device for diffusing rays from said light emitting elements, to equalize luminance of rays from each light emitting element; and

a converging lens system for projecting rays from said light emitting elements onto said photosensitive material, wherein each of said light emitting elements is assigned to record a dot at a time when driven in synchronism with the conveying movement of said photosensitive material, thereby to print said latent image line by line.

2. An optical printing head as recited in claim 1, further comprising a mask plate disposed between said diffusion device and said converging lens system, said mask plate having openings in correspondence with said light emitting elements, said

Sub,  
Bent

openings limiting heading directions of the rays from said light emitting elements and having a shape corresponding to an expected shape of said dot.

5           3. An optical printing head as recited in claim 1, wherein said partitioning device comprises a plurality of thin plates placed between said light emitting elements.

10           4. An optical printing head as recited in claim 3, wherein spaces between said thin plates are filled up with a transparent coating material to coat said light emitting elements.

15           5. An optical printing head as recited in claim 4, wherein said diffusion device comprises light diffusing particles mixed into said coating material.

20           6. An optical printing head as recited in claim 1, wherein said partitioning device comprises a thick plate having openings for exposing said light emitting elements.

25           7. An optical printing head as recited in claim 6, wherein said openings of said thick plate are filled up with a transparent coating material to coat said light emitting elements.

          8. An optical printing head as recited in claim 7, wherein said diffusion device comprises light diffusing particles mixed into said transparent coating material.

Sub,  
B cont

9. An optical printing head as recited in claim 1, wherein said diffusion device is a diffusion plate mounted on said partitioning device, to cover up all of said light emitting elements.

5

10. An optical printing head as recited in claim 1, wherein said light emitting elements are arranged in a plurality of rows, each row extending in the perpendicular direction to the conveying direction of said photosensitive material.

10

11. An optical printing head as recited in claim 10, wherein said light emitting elements of each row are spaced from each other by a distance that is equal to or slightly less than a length of each light emitting element in the perpendicular direction to the conveying direction of said photosensitive material, and said light emitting elements of one row are staggered from those of adjacent rows in said perpendicular direction by an amount approximately equal to said distance.

15

20

12. An optical printing head as recited in claim 11, wherein adjacent two rows of said light emitting elements are paired to emit rays of a different color from other pairs of rows of said light emitting elements, thereby to print said latent image in different colors.

25

13. An optical printing head as recited in claim 10, wherein said light emitting elements are aligned in both widthwise and lengthwise directions of said photosensitive



Sub  
B, cont

photosensitive material, thereby to print said latent image line by line in said three colors.

15 15. An optical printing head as recited in claim 14,  
wherein each of said light emitting element array units further  
comprises a mask plate disposed on an opposite side of said  
diffusion device from said light emitting elements, said mask  
plate having openings in correspondence with said light  
10 emitting elements, said openings limiting heading directions  
of the rays from said light emitting elements and having a shape  
corresponding to an expected shape of said dot.

15 16. A side-printing device for printing data of a  
photosensitive material as a latent image on a side margin of  
said photosensitive material while said photosensitive  
material is being conveyed in a direction, said side-printing  
device comprising three optical printing heads for emitting  
rays of three colors respectively, each of said optical printing  
heads comprising:

20 a plurality of light emitting elements mounted on a  
substrate and arranged along a perpendicular direction to the  
conveying direction of said photosensitive material, said light  
emitting elements emitting rays of one of said three colors;

25 a partitioning device mounted on said substrate, for  
partitioning said light emitting elements from each other;

a diffusion device for diffusing rays from said light  
emitting elements; and

5 a converging lens system for projecting rays from said light emitting elements onto said photosensitive material, wherein each of said light emitting elements of said three optical printing heads is assigned to record a dot of one color at a time when driven in synchronism with the conveying movement of said photo sensitive material, thereby to print said latent image line by line in said three colors.

17. A side-printing device as recited in claim 16, each  
10 of said optical printing heads further comprises a mask plate  
disposed between said diffusion device and said converging lens  
system, said mask plate having openings in correspondence with  
said light emitting elements, said openings limiting heading  
directions of the rays from said light emitting elements and  
15 having a shape corresponding to an expected shape of said dot.

**SECRET**